







ENTERPRISE AND  
DESKTOP MFPs

 **Color A3 MFP**

 **Black-and-White A3 MFP**

| Color A3 MFP  |   |   | Black-and-White A3 MFP  |  |   |
|---|---|---|---|--|---|
| <br>imageRUNNER ADVANCE DX<br>C7780i: 80/70 ppm<br>C7770i: 70/65 ppm<br>C7765i: 65/60 ppm | <br>imageRUNNER ADVANCE DX<br>C5760i: 60/60 ppm<br>C5750i: 50/50 ppm<br>C5740i: 40/40 ppm<br>C5735i: 35/35 ppm | <br>imageRUNNER ADVANCE DX<br>C3730i: 30/30 ppm<br>C3725i: 25/25 ppm | <br>imageRUNNER ADVANCE DX<br>8705i: 105 ppm<br>8795i: 95 ppm<br>8786i: 86 ppm | <br>imageRUNNER ADVANCE DX<br>6780i: 80 ppm<br>6765i: 65 ppm<br>6755i: 55 ppm | <br>imageRUNNER ADVANCE DX<br>475li: 51 ppm<br>4745i: 45 ppm<br>4735i: 35 ppm*<br>4725i: 25 ppm* |

| SPECIFICATIONS                                      |             |             |             |             |             |               |
|---|-------------|-------------|-------------|-------------|-------------|---------------|
| Copy/Scan/Send                                      | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| Single-Pass Duplex ADF                              | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| Scan Speed  | 270/270 ipm | 270/270 ipm | 270/270 ipm | 270/270 ipm | 270/270 ipm | 270/270 ipm** |
| Print - PCL   | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| Print - PS  | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| Fax   | Optional    | Optional    | Optional    | Optional    | Optional    | Optional      |
| Remote Operator's Software                          | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| MEAP  | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| ULM (imageRUNNER ADVANCE)                           | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| uniFLOW Online Express^                             | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| SIEM Integration                                    | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |
| Verify System at Startup*/ McAfee Embedded Control^ | ✓           | ✓           | ✓           | ✓           | ✓           | ✓             |

NOTES: Output speeds reflect maximum number of pages per minute in BW/Color; scanning speeds based on max./min. speed at 300 dpi in BW/Color and duplex, unless otherwise stated. All imageRUNNER ADVANCE models support optional uniFLOW. Check for availability and details for uniFLOW solutions. For imageRUNNER ADVANCE models, update to the latest version of the Unified Firmware Platform for access to all available features. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon, imageRUNNER, and imageCLASS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. McAfee is a trademark of McAfee LLC in the US and/or other countries. Products are current models as of March 2020, and some may be shown with optional accessories. Specifications and availability subject to change without notice. Not responsible for typographical errors.  
©2020 Canon U.S.A., Inc. All rights reserved.

\* Single-Pass Duplex ADF and Duplexing ADF are optional on the imageRUNNER ADVANCE DX 4735i/4725i.  
\*\* When configured with the optional Duplexing ADF, the imageRUNNER ADVANCE DX 4735i/4725i scan speed is 35 ipm (BW/Color).  
▲ Included with main unit; however, activation is required. Check for interoperability with other third-party solutions.  
■ Available on imageRUNNER ADVANCE third edition and imageRUNNER ADVANCE DX models only. Verify System at Start Up and McAfee Embedded Control are set to [Off] by default. Each can be turned on by an administrator in Settings/Registration. When Verify System at Startup is set to ON, device startup will increase by 20-40 seconds (depending on the model). Recovery from Sleep Mode is not affected. This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.



ENTERPRISE AND  
DESKTOP MFPs



|   | Color A4   |  | Black-and-White A4 |  |   |
|---|--|--|--------------------|--|---|
|   | <div></div> <div>imageRUNNER ADVANCE<br/>C475iF III: 50/50 ppm<br/>C475iFZ III:▲ 50/50 ppm</div> | <div></div> <div>imageRUNNER ADVANCE<br/>C356iF III: 36/36 ppm<br/>C256iF III: 26/26 ppm</div> |                    | <div></div> <div>imageRUNNER ADVANCE<br/>715iF III/715iFZ III:▲ 75 ppm<br/>615iF III/615iFZ III:▲ 65 ppm<br/>525iF III/525iFZ III:▲ 55 ppm</div> | <div></div> <div>imageRUNNER<br/>1643i: 45 ppm   1643iF: 45 ppm</div> |
| SPECIFICATIONS  |  |  |                    |  |   |
| Copy/Scan/Send  | ✓  | ✓  | ✓                  | ✓  |   |
| Single-Pass Duplex ADF  | ✓  | ✓  | ✓                  | N/A  |   |
| Scan Speed  | 100/100 ipm  | 100/100 ipm  | 100/100 ipm        | 70/26 ipm  |   |
| Print - PCL   | ✓  | ✓  | ✓                  | ✓  |   |
| Print - PS  | ✓  | ✓  | ✓                  | Optional   | ✓   |
| Fax   | ✓  | ✓  | ✓                  | N/A  | ✓   |
| Remote Operator's Software                                    | ✓  | ✓  | ✓                  | N/A  |   |
| MEAP  | ✓  | ✓  | ✓                  | N/A  |   |
| ULM (imageRUNNER ADVANCE)▲▲<br>eULM (imageRUNNER, imageCLASS) | ✓  | ✓  | ✓                  | ✓  |   |
| uniFLOW Online Express▲▲▲                                     | ✓  | ✓  | ✓                  | ✓  |   |
| SIEM Integration  | ✓  | ✓  | ✓                  | N/A  |   |
| Verify System at Startup*                                     | ✓  | ✓  | ✓                  | ✓  |   |
| McAfee Embedded Control*                                      | ✓  | ✓  | ✓                  | N/A  |   |

NOTES: Output speeds reflect maximum number of pages per minute in BW/Color; scanning speeds based on max./min. speed at 300 dpi in BW/Color and duplex, unless otherwise stated. All imageRUNNER ADVANCE models support optional uniFLOW. Check for availability and details for uniFLOW solutions. For imageRUNNER ADVANCE models, update to the latest version of the Unified Firmware Platform for access to all available features. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon, imageRUNNER, and imageCLASS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. McAfee is a trademark of McAfee LLC in the US and/or other countries. Products are current models as of May 2020, and some may be shown with optional accessories. Specifications and availability subject to change without notice. Not responsible for typographical errors.  
©2020 Canon U.S.A., Inc. All rights reserved.

▲ iFZ III models include standard finish  
▲▲ Requires free download.  
▲▲▲ Included with main unit; however, activation required  
■ Available on imageRUNNER ADVANCE models. Requires the "Verify System at Start Up and McAfee Embedded Control" option to be selected in the Settings/Registration menu. Activation time is approximately 20-40 seconds (depending on the model) and must be turned on by the user.