

ENTERPRISE AND DESKTOP MFPs

Color A3 MFP Black-and-White A3 MFP

Color A3 MFP	Black-and-White A3 MFP					
<p>imagePRESS Lite C270: 80/70 ppm C265: 70/65 ppm</p>	<p>imageRUNNER ADVANCE DX C5870i: 70/70 ppm C5860i: 60/60 ppm C5850i: 50/50 ppm C5840i: 40/40 ppm</p>	<p>imageRUNNER ADVANCE DX C3835i: 35 ppm C3830i: 30 ppm C3826i: 26 ppm</p>	<p>imageRUNNER ADVANCE DX 8705i: 105 ppm 8795i: 95 ppm 8786i: 86 ppm</p>	<p>imageRUNNER ADVANCE DX 6870i: 70 ppm 6860i: 60 ppm 6855i: 55 ppm</p>	<p>imageRUNNER ADVANCE DX 6780i: 80 ppm</p>	<p>imageRUNNER ADVANCE DX 4845i: 45 ppm 4835i: 35 ppm* 4825i: 25 ppm*</p>

SPECIFICATIONS							
Copy/Scan/Send	✓	✓	✓	✓	✓	✓	✓
Single-Pass Duplex ADF	✓	✓	✓	✓	✓	✓	✓
Scan Speed	270/270 ipm	270/270 ipm	270/270 ipm	270/270 ipm	270/270 ipm	270/270 ipm	270/270 ipm**
Print - PCL	✓	✓	✓	✓	✓	✓	✓
Print - PS	✓	✓	✓	✓	✓	✓	✓
Fax	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Remote Operator's Software	✓	✓	✓	✓	✓	✓	✓
MEAP	✓	✓	✓	✓	✓	✓	✓
ULM (imageRUNNER ADVANCE)	✓	✓	✓	✓	✓	✓	✓
uniFLOW Online Express [^]	✓	✓	✓	✓	✓	✓	✓
SIEM Integration	✓	✓	✓	✓	✓	✓	✓
Verify System at Startup/McAfee Embedded Control [^]	✓	✓	✓	✓	✓	✓	✓

NOTES: Output speeds reflect maximum number of pages per minute in BW/Color; scanning speeds based on 300 dpi in BW/Color and duplex, unless otherwise stated. All imageRUNNER ADVANCE models support optional uniFLOW. Check for availability and details for uniFLOW solutions. For imageRUNNER ADVANCE models, update to the latest version of the Unified Firmware Platform for access to all available features. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon, imageRUNNER, imagePRESS, and imageCLASS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. McAfee is a trademark of McAfee LLC in the US and/or other countries. Products are current models as of May 2022, and some may be shown with optional accessories. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2022 Canon U.S.A., Inc. All rights reserved.

* Single-Pass Duplex ADF and Duplexing ADF are optional on the imageRUNNER ADVANCE DX 4735i/4725i.
 ** When configured with the optional Single Pass Duplexing Automatic Document Feeder, the imageRUNNER ADVANCE DX 4735i/4725i scan speed is 35 ipm (BW/Color).
[^] Included with main unit; however, activation is required. Check for interoperability with other third-party solutions.
[^] Verify System at Start Up and McAfee Embedded Control are set to [Off] by default. Each can be turned on by an administrator in Settings/Registration. When Verify System at Startup is set to ON, device startup will increase by 20-40 seconds (depending on the model). Recovery from Sleep Mode is not affected. This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.

ENTERPRISE AND DESKTOP MFPs

Color A4
Black-and-White A4

	Color A4					Color A4 Inkjet	Black-and-White A4		

SPECIFICATIONS									
Copy/Scan/Send	✓	✓	✓	✓	✓	✓	✓	✓	✓
Single-Pass Duplex ADF	✓	✓	✓	✓	✓	✓	✓	✓	✓
Scan Speed	200/200 ipm	200/200 ipm	155/150 ipm	40/20 ipm	51/27 ipm	22.2/12.2ipm	200/200 ipm	70/26 ipm	70/26 ipm
Print - PCL	✓	✓	✓	✓	✓	N/A	✓	✓	✓
Print - PS	✓	✓	✓	✓	✓	N/A	✓	Optional	✓
Fax	✓	✓	✓	✓	✓	✓	✓	N/A	✓
Remote Operator's Software	✓	✓	✓	N/A	N/A	N/A	✓	N/A	N/A
MEAP	✓	✓	N/A	N/A	N/A	N/A	✓	N/A	N/A
ULM (imageRUNNER ADVANCE)* eULM (imageRUNNER, imageCLASS)	✓	✓	✓	✓	✓	N/A	✓	✓	✓
uniFLOW Online Express**	✓	✓	✓	✓	✓	N/A Optional uniFLOW Cloud Link Print Connection.▲	✓	✓	✓
SIEM Integration	✓	✓	N/A	N/A	N/A	N/A	✓	N/A	N/A
Verify System at Startup	✓	✓	✓	✓	✓	N/A	✓	✓	✓
McAfee Embedded Control[®]	✓	✓	N/A	N/A	N/A	N/A	✓	N/A	N/A

NOTES: Output speeds reflect maximum number of pages per minute in BW/Color; scanning speeds based on 300 dpi in BW/Color and duplex, unless otherwise stated. All imageRUNNER ADVANCE models support optional uniFLOW. Check for availability and details for uniFLOW solutions. For imageRUNNER ADVANCE models, update to the latest version of the Unified Firmware Platform for access to all available features. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon, imageRUNNER, imagePRESS, imageCLASS, and MAXIFY are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. McAfee is a trademark of McAfee LLC in the US and/or other countries. Products are current models as of May 2022, and some may be shown with optional accessories. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2022 Canon U.S.A., Inc. All rights reserved.

* Requires free download.

** Included with main unit; however, activation is required. Check for interoperability with other third-party solutions.

▲ Cloud Link Print Connection is a user-based license. The subscription of at least one uniFLOW Online Cloud Print & Scan or Image Processing License is required. Reporting requires the use/selection of the uniFLOW Online Cloud Link Print Connection print driver. Canon offers products that contain certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Some security features may impact functionality/performance; you may want to test these settings in your environment.

■ Verify System at Start Up and McAfee Embedded Control are set to [Off] by default. Each can be turned on by an administrator in Settings/Registration. When Verify System at Startup is set to ON, device startup will increase by 20-40 seconds (depending on the model). Recovery from Sleep Mode is not affected. This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.

Canon Recommended Monthly Volumes

imageCLASS, imageRUNNER Advance, & Production

01/18/2023

<u>B&W Models</u>	PPM	Optimum Zone	Max Duty Cycle
<u>"A4 B&W"</u>			
<i>imageCLASS B&W A4</i>			
LBP1238 II <i>Printer</i>	40	500-4,000	80K
LBP325dn <i>Printer</i>	45	1,500-7,500	150K
LBP1871 <i>Printer</i>	75	5,000-30,000	450K
LBP1861 <i>Printer</i>	65	5,000-20,000	420K
MF1238 II <i>MFP</i>	40	500-4,000	80K
MF1643i II <i>MFP (no Fax)</i>	45	1,500-20,000	150K
MF1643iF II <i>MFP</i>	45	1,500-20,000	150K
<i>iR ADV B&W A4</i>			
iR ADV DX 527iF / iFZ	55	3K-35K	250K
iR ADV DX 617iF / iFZ	65	3K-37K	275K
iR ADV DX 717iF / iFZ	75	3K-40K	300K

<u>COLOR Models</u>	PPM B&W/COLOR	Optimum Zone	Max Duty Cycle
<u>"A4 Color"</u>			
<i>imageCLASS Color A4</i>			
LBP1333C <i>Printer</i>	35/35	750-4,000	50K
LBP1538C <i>Printer</i>	40/40	2,000-10,000	80K
MF1333C <i>MFP</i>	35/35	750-4,000	50K
MF1538C <i>MFP</i>	40/40	2,000-10,000	80K
<i>iR ADV Color A4</i>			
iR ADV DX C257iF	26/26	1K-10K	70K
iR ADV DX C357iF	36/36	1K-10K	90K
iR ADV DX C478iF / iFZ	50/50	1K-10K	100K
iR ADV DX C568iF / iFZ	60/60	1K-10K	120K

<u>"A3 B&W"</u>			
iR ADV DX 4825i	25	3K-40K	95K
iR ADV DX 4835i	35	5K-45K	135K
iR ADV DX 4845i	45	5K-65K	170K
<hr/>			
iR ADV DX 6855i	55	5K-65K	215K
iR ADV DX 6860i	60	12K-70K	300K
iR ADV DX 6870i	70	20K-70K	350K
<hr/>			
iR ADV DX 6780i	80	30K-150K	350K
iR ADV DX 8786i	86	40K-200K	750K
iR ADV DX 8795i	95	60K-250K	900K
iR ADV DX 8705i	105	80K-300K	1 million

<u>"A3 Color"</u>			
iR ADV DX C3826i	26/26	2K-16K	115K
iR ADV DX C3830i	30/30	2K-16K	130K
iR ADV DX C3835i	35/35	2K-30K	150K
<hr/>			
iR ADV DX C5840i	40/40	5K-45K	170K
iR ADV DX C5850i	50/50	10K-50K	185K
iR ADV DX C5860i	60/60	12K-60K	230K
iR ADV DX C5870i	70/70	14K-80K	350K

<u>"imagePRESS LITE"</u>			
imagePRESS Lite C265	70/65	15K-100K	330K
imagePRESS Lite C270	80/70	15K-120K	390K

<u>"B&W Production"</u>			
varioPRINT 115	115	80K-800K	1.7 million
varioPRINT 130	130	150K-800K	2.2 million
varioPRINT 140	140	200K-800K	2.2 million
<hr/>			
TITAN 6180	177	300K-2.5M	2.5 million
TITAN 6220	216	500K-5M	5.0 million
TITAN 6270	266	750K-8M	8.0 million
TITAN 6330	320	1M-10M	10.0 million

<u>"Color Production"</u>			
imagePRESS C710	70/70	5K-125K	350K
imagePRESS C810	80/80	30K-125K	400K
imagePRESS C910	90/90	40K-167K	500K
imagePRESS V700 <i>Jan 23</i>	71/71	5K-190K	350K
imagePRESS V800 <i>Jan 23</i>	81/81	30K-220K	400K
imagePRESS V900 <i>Jan 23</i>	90/90	40K-250K	500K
imagePRESS V1000	101/101	75K-600K	1.2 mil
imagePRESS V1350 <i>Feb23</i>	135/135	<i>Coming</i>	<i>March 2023</i>

Canon publishes two different guidelines for monthly volume expectations, unlike most other manufacturers who only publish a maximum duty cycle. Here are the definitions:

Optimum Zone: Canon Engineering's recommended range for optimal performance and maximum performance.

- **Guideline** - - Stay in the middle of the Optimum Zone for the best long-term performance.

Max Duty Cycle: While they may occasionally produce these volumes, sustained use could affect long-term performance and durability.

- **Guideline** - - Use only when responding to a BID/RFP since Competitors will quote their own "maximum duty cycle".